

TRIMAT

CARROSSIER FRIGORIFIQUE



Isothermal and refrigerated
bodywork for

VOLKSWAGEN ID BUZZ CARGO



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD




MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Integrated isothermal cell

VOLKSWAGEN ID BUZZ CARGO

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions:

- Short bed L1 panel van, wheelbase 2989 mm with right side door.
- Retain the original windowless bulkhead for enhanced safety, swinging rear panel doors, right-side sliding door.

TRIMAT ISOKIT insulation and bodywork

- Integrated ATP-quality "Reinforced Class" isothermal container with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

Electric refrigeration units (CARRIER, THERMOKING, VESNA V-BOX, EDT, etc.)

Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit.

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Aerodynamic, semi-recessed installation above the roof or against the roof.
- Cooling unit option: dual road/230V single-phase grid power mode with electrical outlet on the driver's side and extension cord, cooling unit fairing paint, heating mode, temperature logger, door contact, Pharma certification, etc.

Catering, distribution, seafood, medical, last-mile delivery configurations, etc.

- Adjustable and liftable shelves, intermediate floor (rear zone only or rear + front), seafood sill, aluminum protective runners, lashing rails, lashing strap, round load stop bar, anti-loss curtain, multi-compartment bulkhead, non-slip mat, grooved aluminum floor, etc.

DIMENSIONS mm	ID BUZZ CARGO
Wheelbase	2989
Max. usable length at floor level	1940
Max. usable width at floor level	1270
Wheel well width	1090
Overall height isotherm / AEROTOP fairing	1920 / 2020
Max. usable height excluding evaporator	1065
Width / Height rear door passage	1090 / 950
Width / Height side door passage	530 / 900
Loading sill height	origin
Weight cell conversion (kg), excluding cooling unit and options	125
Usable volume (m3)	2.13



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified qualified
operator



Our facilities comply
with the HACCP
hygiene method