

TRIMAT

CARROSSIER FRIGORIFIQUE



Isothermal and refrigerated
bodywork for
FORD CONNECT



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

**DESIGNED AND
MANUFACTURED
IN FRANCE**



Integrated isothermal cell

FORD CONNECT

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions:

- L1H1 panel van (wheelbase 2662 mm) with or without right side door.
- L2H1 panel van (wheelbase 3062 mm) with or without right side door.
- Retain the original windowless bulkhead for enhanced safety, swing rear panel doors, right-side sliding door.
- Compatibility: original trailer hitch installed before conversion.

TRIMAT ISOKIT insulation and bodywork

- ATP-quality "Reinforced Class" integrated isothermal cell with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan with front left drain.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

Refrigeration units (CARRIER, THERMOKING, VESNA V-BOX, EDT, etc.)

Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit. The configuration of the base vehicle must be specified when ordering.

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Aerodynamic semi-recessed installation above roof, on roof or sub-frame, in-cab touch control.
- Cooling unit option: road/grid power, heating mode, temperature logger, "Pharma" certification, AEROTOP fairing painting, etc.

Catering, distribution, seafood, medical, last-mile delivery configurations, etc.

- Adjustable and liftable shelves, intermediate floor (rear zone only or rear + front), seafood sill, aluminum protective runner, lashing rails, lashing strap, round load stop bar.

▲ Provide the reinforced floor option for the use of a rolling cart (roller, pallet truck, etc.)

DIMENSIONS mm	L1	L2
Wheelbase	2662	3062
Overall length	4418	4818
Max. usable length at floor level	1440	1840
Wheel well width	1065	1065
Overall height isotherm / AEROTOP fairing	1860 / 2032	1860 / 2032
Max. usable height excluding evaporator	1025	1025
Width / Height rear door passage	1065 / 955	1065 / 955
Width / Height side door passage		480-630 / 865
Loading sill height	origin	origin
Weight cell conversion (kg), excluding cooling unit and options	95	120
Usable volume (m3)	1.60	2.20



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method

