

**TRIMAT**

CARROSSIER FRIGORIFIQUE



**IVECO**

Isothermal and refrigerated  
bodywork for

**IVECO DAILY**



[www.trimat-kit.com](http://www.trimat-kit.com)



**DESIGNER AND MANUFACTURER**

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND  
MANUFACTURED  
IN FRANCE



## Integrated isothermal cell

## IVECO DAILY

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

**Versions:**

- V11 L2H2 RWD panel van (wheelbase 3520 S mm) with or without right side door.
- V12 L3H2 RWD panel van (wheelbase 3520 L mm) with or without right side door.
- V16 L4H2 RWD panel van (wheelbase 4100 mm) with or without right side door.
- NB: with complete cab bulkhead, available with single or dual rear wheels.
- Compatibility: Original trailer hitch installed before conversion.

**TRIMAT ISOKIT insulation and bodywork**

- ATP-quality "Reinforced Class" integrated isothermal cell with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan with front left drain.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

**Refrigeration units (CARRIER, THERMOKING, EDT, etc.)**

**Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit. The configuration of the base vehicle must be specified when ordering.**

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Recessed mounting above cab and touch control on the dashboard.
- Cooling unit option: Dual-mode road/grid power, heating mode, temperature logger, "Pharma" certification, multi-temperature, cooling unit cover painting, etc.

**Catering, distribution, seafood, medical, last-mile delivery configurations, etc.**

- Adjustable and liftable shelves, intermediate floor (single rear zone or back + front), seafood sill, aluminum protective runners, lashing rails, lashing strap, round load stop bar, anti-loss curtain, multi-compartment bulkhead, non-slip mat, grooved aluminum floor, etc.

**▲ Provide the reinforced floor option for the use of a rolling cart (roller, pallet truck, etc.)**

DIMENSIONS mm	V11 L2H2	V12 L3H2	V16 L4H2
Wheelbase	3520 S	3520 L	4100
Overall length	5558	5963	7128
Max. usable length at floor level	2943	3341	4485
Max. usable width at floor level	1603	1603	1603
Wheel well width - single wheels	1213	1213	1213
Wheel well width - dual wheels	945	945	945
Max. usable height excluding evaporator	1745	1745	1745
Width / Height rear door passage	1290 / 1591	1290 / 1591	1290 / 1591
Width / Height side door passage	1089-1116 / 1612	1089-1116 / 1612	1089-1116 / 1612
Loading sill height	origin	origin	origin
Weight cell conversion (kg), excluding cooling unit and options	220	240	280
Usable volume (m3)	7.65	8.70	11.70



Cemafruid  
certification  
No. D14/001



TRIMAT is  
a UTAC-certified  
qualified operator



Our facilities comply  
with the HACCP  
hygiene method

