


TRIMAT

CARROSSIER FRIGORIFIQUE



Isothermal and refrigerated
bodywork for

RENAULT EXPRESS VAN



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Integrated isothermal cell

RENAULT EXPRESS VAN

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions:

- L1 panel van (L1, wheelbase 2812 mm) with or without right side door.
- Retain the original windowless bulkhead for enhanced safety, swing rear panel doors, right-side sliding door.
- Compatibility: Original trailer hitch installed before conversion.

TRIMAT ISOKIT insulation and bodywork

- ATP-quality "Reinforced Class" integrated isothermal cell with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan with front left drain.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

Refrigeration units (CARRIER, THERMOKING, VESNA V-BOX, EDT, etc.)

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Aerodynamic, semi-recessed installation above the roof, against the roof or sub-frame.
- Cooling unit option: road/grid power, heating mode, temperature logger, "Pharma" certification, AEROTOP fairing painting, etc.

Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit. The configuration of the base vehicle must be specified when ordering.

Catering, distribution, seafood, medical, last-mile delivery configurations, etc.

- Adjustable and liftable shelves, intermediate floor (single rear zone or back + front), seafood sill, aluminum protective runners, lashing rails, lashing strap, round load stop bar, anti-loss curtain, multi-compartment bulkhead, non-slip mat, grooved aluminum floor, etc.

▲ Provide the reinforced floor option for the use of a rolling cart (roller, pallet truck, etc.)

DIMENSIONS mm	L1
Wheelbase	2812
Overall length	4403
Max. usable length at floor level	1595
Max. usable width	1195
Overall width (with and without rearview mirrors)	2100 / 1920
Wheel well width	1008
Overall height isotherm / AEROTOP fairing	1820 / 2000
Max. usable height excluding evaporator	1040
Width / Height rear door passage	1008 / 938
Width / Height side door passage	384-595 / 837
Loading sill height	origin
Weight cell conversion (kg), excluding cooling unit and options	100
Usable volume (m3)	1.70



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method