


TRIMAT

CARROSSIER FRIGORIFIQUE

ISOBOX



Isothermal and refrigerated
bodywork for cab chassis

**RENAULT
MASTER XDD**



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Isothermal and refrigerated bodywork for cab chassis

RENAULT MASTER XDD

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions :

- FWD L2H1 GVWR 3.5 tons, single rear wheel.
- FWD L3H1 GVWR 3.5 tons, single rear wheel.
- Compatibility: OEM trailer hitch can be installed before conversion.

Bodywork & Insulation – ISOBOX TRIMAT

- ATP quality “REINFORCED isothermal” refrigerated box, with or without side door. Airtight system made of one-piece molded composite panels (TRIMAT tech & manufacture). Insulating polyurethane core and white antibacterial gel-coat outer walls. Gray corundum floor with front-left drainage.
- Standard equipment: Full rear double-door opening. 3-sided aluminum kick plate. Retractable rear step. LED lighting.

Refrigeration units (CARRIER, THERMOKING, ...)

Please consult us in advance to confirm compatibility, availability, and sizing.

Vehicle configuration must be confirmed at the time of order.

- Cooling unit: Positive (Class A) or Negative (Class C) temperature.
- Option de groupe : Dual-mode (road & mains). Heating mode. Temperature recorder. “Pharma” certification. Multi-temperature. Group compartment painting. etc.

Custom interior fittings – For catering, delivery, fish trade, healthcare, last-mile ...

- Adjustable and foldable shelves. Intermediate floor (rear only or full length). Fish trade threshold. Aluminum protection rail. Load securing rails & straps. Round bar load stops. Thermal curtain. Partition wall for multi-compartments. Anti-slip mats. Ribbed aluminum floor. etc.

DIMENSIONS	L2H1	L3H1
Wheelbase	3586 mm	4216 mm
Overall length	5730 / 6169 mm	6269 / 6669 mm
Max internal floor length	3000 / 3500 mm	3600 / 4000 mm
Overall width (no mirrors)	2120 mm	2120 mm
Max internal floor width	1950 mm	1950 mm
Rear door opening (W/H)	1950 / 1950 mm	1950 / 1950 mm
Side door opening (W/H)	900 / 900 mm	900 / 900 mm
Overall height	2975 mm	2975 mm
Loading height	932 mm	932 mm
Body weight	Upon preliminary study	
Usable volume	11.30 / 13.30 m³	13.60 / 15.20 m³



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method