

**TRIMAT**

CARROSSIER FRIGORIFIQUE

**ISOBOX**



**MAXUS**

Isothermal and refrigerated  
bodywork for cab chassis

# MAXUS Deliver 9 et eDeliver 9



[www.trimat-kit.com](http://www.trimat-kit.com)



## DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals  
combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND  
MANUFACTURED  
IN FRANCE



## Isothermal and refrigerated bodywork for cab chassis

## MAXUS Deliver 9 et eDeliver 9

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

**Versions :**

- FWD L2.5H1 GVWR 3.5 tons with single rear wheel
- FWD L3H1 GVWR 3.5 tons with single rear wheel
- Compatibility: OEM trailer hitch can be installed before conversion.

**Bodywork & Insulation – ISOBOX TRIMAT**

- ATP quality “REINFORCED isothermal” refrigerated box, with or without side door. Airtight system made of one-piece molded composite panels (TRIMAT tech & manufacture). Insulating polyurethane core and white antibacterial gel-coat outer walls. Gray corundum floor with front-left drainage.
- Standard equipment: Full rear double-door opening. 3-sided aluminum kick plate. Retractable rear step. LED lighting.

**Refrigeration units (CARRIER, THERMOKING, ...)**

Please consult us in advance to confirm compatibility, availability, and sizing.

Vehicle configuration must be confirmed at the time of order.

- Cooling unit: Positive (Class A) or Negative (Class C) temperature.
- Option de groupe : Dual-mode (road & mains). Heating mode. Temperature recorder. “Pharma” certification. Multi-temperature. Group compartment painting. etc.

**Custom interior fittings – For catering, delivery, fish trade, healthcare, last-mile ...**

- Adjustable and foldable shelves. Intermediate floor (rear only or full length). Fish trade threshold. Aluminum protection rail. Load securing rails & straps. Round bar load stops. Thermal curtain. Partition wall for multi-compartments. Anti-slip mats. Ribbed aluminum floor. etc.

DIMENSIONS	L2.5 H1	L3H1
Wheelbase	3760 mm	3760 mm
Overall length	5820 / 6160 mm	6200 / 6660 mm
Max internal floor length	3000 / 3500 mm	3500 / 4000 mm
Overall width (no mirrors)	2115 mm	2115 mm
Max internal floor width	1950 mm	1950 mm
Rear door opening (W/H)	1945 / 1945 mm	1945 / 1945 mm
Side door opening (W/H)	900 / 1850 mm	900 / 1850 mm
Overall height	2985 mm	2985 mm
Loading height	950 mm	950 mm
Body weight	610 kg / 675 kg	675 kg / 740 kg
Usable volume	11,4 m³ / 13,3 m³	13,3 m³ / 15,2 m³



Cemafruid  
certification  
No. D14/001



TRIMAT is  
a UTAC-certified  
qualified operator



Our facilities comply  
with the HACCP  
hygiene method