

TRIMAT

CARROSSIER FRIGORIFIQUE

ISOBOX



Mercedes-Benz

Isothermal and refrigerated
bodywork for cab chassis

**MERCEDES-BENZ
SPRINTER**



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Isothermal and refrigerated bodywork for cab chassis

MERCEDES-BENZ SPRINTER

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions :

- Rear-wheel drive L2 H1 GVWR 3.5 tonnes single rear wheel
- Rear-wheel drive L3 H1 GVWR 3.5 tonnes single rear wheel
- Compatibility: OEM trailer hitch can be installed before conversion

Bodywork & Insulation – ISOBOX TRIMAT

- ATP quality "REINFORCED isothermal" refrigerated box, with or without side door. Airtight system made of one-piece molded composite panels (TRIMAT tech & manufacture). Insulating polyurethane core and white antibacterial gel-coat outer walls. Gray corundum floor with front-left drainage.
- Standard equipment: Full rear double-door opening. 3-sided aluminum kick plate. Retractable rear step. LED lighting.

Refrigeration units (CARRIER, THERMOKING, ...)

Please consult us in advance to confirm compatibility, availability, and sizing.

Vehicle configuration must be confirmed at the time of order.

- Cooling unit: Positive (Class A) or Negative (Class C) temperature.
- Group option: Dual-mode (road & mains). Heating mode. Temperature recorder. "Pharma" certification. Multi-temperature. Group compartment painting. etc.

Custom interior fittings – For catering, delivery, fish trade, healthcare, last-mile ...

- Adjustable and foldable shelves. Intermediate floor (rear only or full length). Fish trade threshold. Aluminum protection rail. Load securing rails & straps. Round bar load stops. Thermal curtain. Partition wall for multi-compartments. Anti-slip mats. Ribbed aluminum floor. etc.

DIMENSIONS	L2	L3
Wheelbase	3665 mm	4325 mm
Overall length	6775 mm	6975 mm
Max internal floor length	3800 mm	4000 mm
Overall width (no mirrors)	2110 mm	2110 mm
Max internal floor width	1950 mm	1950 mm
Rear door opening (W/H)	1950 x 1950 mm	1950 x 1950 mm
Side door opening (W/H)	900 x 1850 mm	900 x 1850 mm
Overall height	3036 mm	3036 mm
Loading height	1006 mm	1006 mm
Body weight	530 kg à 590 kg	600 kg à 625 kg
Usable volume	11,4 à 14,4 m ³	14,8 à 15,2 m ³



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method