

TRIMAT

CARROSSIER FRIGORIFIQUE



IVECO

Isothermal and refrigerated
bodywork for cab chassis

IVECO DAILY



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Isothermal and refrigerated bodywork for cab chassis

IVECO DAILY

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions :

- Rear-wheel drive L2 H1 GVWR 3.5 tonnes, single and dual wheels
- Rear-wheel drive L3 H1 GVWR 3.5 tonnes, single and dual wheels
- Compatibility: OEM trailer hitch can be installed before conversion

Bodywork & Insulation – ISOBOX TRIMAT

- ATP quality "REINFORCED isothermal" refrigerated box, with or without side door. Airtight system made of one-piece molded composite panels (TRIMAT tech & manufacture). Insulating polyurethane core and white antibacterial gel-coat outer walls. Gray corundum floor with front-left drainage.
- Standard equipment: Full rear double-door opening. 3-sided aluminum kick plate. Retractable rear step. LED lighting.

Refrigeration units (CARRIER, THERMOKING, ...)

Please consult us in advance to confirm compatibility, availability, and sizing.

Vehicle configuration must be confirmed at the time of order.

- Cooling unit: Positive (Class A) or Negative (Class C) temperature.
- Group option: Dual-mode (road & mains). Heating mode. Temperature recorder. "Pharma" certification. Multi-temperature. Group compartment painting. etc.

Custom interior fittings – For catering, delivery, fish trade, healthcare, last-mile ...

- Adjustable and foldable shelves. Intermediate floor (rear only or full length). Fish trade threshold. Aluminum protection rail. Load securing rails & straps. Round bar load stops. Thermal curtain. Partition wall for multi-compartments. Anti-slip mats. Ribbed aluminum floor. etc.

DIMENSIONS	L2	L3
Wheelbase	3450 mm	3750 mm
Overall length	5983 à 6093 mm	6593 à 6693 mm
Max internal floor length	3100 à 3400 mm	3500 à 3900 mm
Overall width (no mirrors)	2115 mm	2115 mm
Max internal floor width	1950 mm	1950 mm
Rear door opening (W/H)	1945 mm	1945 mm
Side door opening (W/H)	1945 mm	1945 mm
Overall height	3045 mm	3045 mm
Loading height	1015 mm	1015 mm
Body weight	600 kg a 650 kg	660 kg à 700 kg
Usable volume	11,7 m ³	14,8 m ³



Cemafrica
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method