

**TRIMAT**

CARROSSIER FRIGORIFIQUE



Isothermal and refrigerated  
bodywork for  
**CITROËN JUMPER**



[www.trimat-kit.com](http://www.trimat-kit.com)



**DESIGNER AND MANUFACTURER**

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND  
MANUFACTURED  
IN FRANCE



## Integrated isothermal cell

## CITROËN JUMPER

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

### Versions:

- L2H1 panel van (wheelbase 3450 mm) with or without right side door.
- L2H2 panel van (wheelbase 3450 mm) with or without right side door.
- L3H2 panel van (wheelbase 4035 mm) with or without right side door.
- J53M refrigeration predisposition with outlet for conversion.
- Compatibility: Original trailer hitch installed before conversion.
- Incompatibility: J2YG worksite pack.

### TRIMAT ISOKIT insulation and bodywork

- ATP-quality "Reinforced Class" integrated isothermal cell with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan with front left drain.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

### Refrigeration units (CARRIER, THERMOKING, EDT, etc.)

**Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit. The configuration of the base vehicle must be specified when ordering.**

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Recessed mounting above the cab and touch control on the dashboard.
- Cooling unit option: Dual-mode road/grid power, heating mode, temperature logger, "Pharma" certification, multi-temperature, cooling unit cover painting, etc.

### Catering, distribution, seafood, medical, last-mile delivery configurations, etc.

- Adjustable and liftable shelves, intermediate floor (single rear zone or back + front), seafood sill, aluminum protective runners, lashing rails, lashing strap, round load stop bar, anti-loss curtain, multi-compartment bulkhead, non-slip mat, grooved aluminum floor, etc.

**▲ Provide the reinforced floor option for the use of a rolling cart (roller, pallet truck, etc.)**

| DIMENSIONS mm                                                   | L2H1            | L2H2             | L3H2             |
|-----------------------------------------------------------------|-----------------|------------------|------------------|
| Wheelbase                                                       | 3450            | 3450             | 4035             |
| Overall length                                                  | 5413            | 5413             | 5998             |
| Max. usable length at floor level                               | 2790            | 2790             | 3400             |
| Max. usable width at floor level                                | 1615            | 1615             | 1615             |
| Wheel well width                                                | 1260            | 1260             | 1260             |
| Max. usable height excluding evaporator                         | 1450            | 1750             | 1750             |
| Width / Height rear door passage                                | 1405 / 1310     | 1405 / 1595      | 1405 / 1595      |
| Width / Height side door passage                                | 985-1010 / 1270 | 1095-1030 / 1560 | 1095-1030 / 1560 |
| Loading sill height                                             | origin          | origin           | origin           |
| Weight cell conversion (kg), excluding cooling unit and options | 200             | 250              | 280              |
| Usable volume (m3)                                              | 6.86            | 7.93             | 9.50             |



Cemafruid  
certification  
No. D14/001



TRIMAT is  
a UTAC-certified  
qualified operator



Our facilities comply  
with the HACCP  
hygiene method

