

TRIMAT

CARROSSIER FRIGORIFIQUE



Isothermal and refrigerated
bodywork for

FORD TRANSIT 2T E-TRANSIT 2T RWD



www.trimat-kit.com



DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND
MANUFACTURED
IN FRANCE



Integrated isothermal cell
FORD TRANSIT 2T - E-TRANSIT 2T RWD

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

Versions:

- L2H2 RWD panel van (wheelbase 3300 mm) with or without right side door.
- L3H2 RWD panel van (wheelbase 3750 mm) with or without right side door.
- L2H3 RWD panel van (wheelbase 3300 mm) with or without right side door.
- L3H3 RWD panel van (wheelbase 3750 mm) with or without right side door.
- **NB:** available with single or dual rear wheels.
- Compatibility: Original trailer hitch installed before conversion.

TRIMAT ISOKIT insulation and bodywork

- ATP-quality "Reinforced Class" integrated isothermal cell with or without side door, consisting of a hermetic system of one-piece molded composite panels produced using TRIMAT manufacturing processes and technology. Insulating polyurethane core and external walls with a white antibacterial gel-coat. Diamond tread flooring forming a pan with front left drain.
- Standard equipment: LED lighting, dual insulating seal on openings, side door seafood sill.

Refrigeration units (CARRIER, THERMOKING, EDT, etc.)

Please consult us beforehand to check the compatibility, timeframe and size of the refrigeration unit. The configuration of the base vehicle must be specified when ordering.

- Class A (positive) or C (negative) cooling unit
- Power and technology (electric or direct drive) adapted according to use. Recessed mounting above cab and touch control on the dashboard.
- Cooling unit option: Dual-mode road/grid power, heating mode, temperature logger, "Pharma" certification, multi-temperature, cooling unit cover painting, etc.

Catering, distribution, seafood, medical, last-mile delivery configurations, etc.

- Adjustable and liftable shelves, intermediate floor (single rear zone or back + front), seafood sill, aluminum protective runners, lashing rails, lashing strap, round load stop bar, anti-loss curtain, multi-compartment bulkhead, non-slip mat, grooved aluminum floor, etc.

▲ Provide the reinforced floor option for the use of a rolling cart (roller, pallet truck, etc.)

DIMENSIONS mm	L2H2 RWD	L3H2 RWD	L2H3 RWD	L3H3 RWD	L4H3 RWD
Wheelbase	3300	3750	3300	3750	3750
Overall length	5531	5981	5531	5981	6704
Max. usable length at floor level	2780	3230	2780	3230	3950
Max. usable width at floor level	1520	1520	1520	1520	1520
Wheel well width - single wheels	1250	1250	1250	1250	1250
Wheel well width - dual wheels	800	800	800	800	800
Max. usable height excluding evaporator	1555	1555	1815	1815	1815
Width / Height rear door passage	1377 / 1460	1377 / 1460	1377 / 1675	1377 / 1675	1377 / 1675
Width / Height side door passage	1100-1170 / 1385	1100-1170 / 1385	1100-1170 / 1385	1100-1170 / 1385	1100-1170 / 1385
Loading sill height	origin	origin	origin	origin	origin
Weight cell conversion (kg), excluding cooling unit and options	210	230	220	240	300
Usable volume (m3)	6.2	7.3	7.2	8.3	10.1



Cemafruid
certification
No. D14/001



TRIMAT is
a UTAC-certified
qualified operator



Our facilities comply
with the HACCP
hygiene method

