

**TRIMAT**

CARROSSIER FRIGORIFIQUE

**ISOBOX**



Isothermal and refrigerated  
bodywork for cab chassis  
**NISSAN INTERSTAR**



[www.trimat-kit.com](http://www.trimat-kit.com)



#### DESIGNER AND MANUFACTURER

Trimat designed a range of isothermal cells for professionals combining functionality, aesthetics and longevity.



FOOD



MEDICAL



SPECIFIC

DESIGNED AND  
MANUFACTURED  
IN FRANCE



**Isothermal and refrigerated bodywork for cab chassis**
**NISSAN INTERSTAR**

This body is intended for temperature-controlled transport in accordance with current ATP regulations.

**Versions :**

- FWD L2H1 GVWR 3.5 tons, single rear wheel.
- FWD L3H1 GVWR 3.5 tons, single rear wheel.
- Compatibility: OEM trailer hitch can be installed before conversion.

**Bodywork & Insulation – ISOBOX TRIMAT**

- ATP quality “REINFORCED isothermal” refrigerated box, with or without side door. Airtight system made of one-piece molded composite panels (TRIMAT tech & manufacture). Insulating polyurethane core and white antibacterial gel-coat outer walls. Gray corundum floor with front-left drainage.
- Standard equipment: Full rear double-door opening. 3-sided aluminum kick plate. Retractable rear step. LED lighting.

**Refrigeration units (CARRIER, THERMOKING, ...)**

**Please consult us in advance to confirm compatibility, availability, and sizing.**

**Vehicle configuration must be confirmed at the time of order.**

- Cooling unit: Positive (Class A) or Negative (Class C) temperature.
- Group option: Dual-mode (road & mains). Heating mode. Temperature recorder. “Pharma” certification. Multi-temperature. Group compartment painting. etc.

**Custom interior fittings – For catering, delivery, fish trade, healthcare, last-mile ...**

- Adjustable and foldable shelves. Intermediate floor (rear only or full length). Fish trade threshold. Aluminum protection rail. Load securing rails & straps. Round bar load stops. Thermal curtain. Partition wall for multi-compartments. Anti-slip mats. Ribbed aluminum floor. etc.

DIMENSIONS	L2H1	L3H1
Wheelbase	3586 mm	4216 mm
Overall length	5730 / 6169 mm	6269 / 6669 mm
Max internal floor length	3000 / 3500 mm	3600 / 4000 mm
Overall width (no mirrors)	2120 mm	2120 mm
Max internal floor width	1950 mm	1950 mm
Rear door opening (W/H)	1950 / 1950 mm	1950 / 1950 mm
Side door opening (W/H)	900 / 900 mm	900 / 900 mm
Overall height	2975 mm	2975 mm
Loading height	932 mm	932 mm
Body weight	Upon preliminary study	
Usable volume	11.30 / 13.30 m <sup>3</sup>	13.60 / 15.20 m <sup>3</sup>



Cemafruid  
certification  
No. D14/001



TRIMAT is  
a UTAC-certified  
qualified operator



Our facilities comply  
with the HACCP  
hygiene method